

Boilere electrice apa calda MIDEA



Specificatii tehnice

MODEL	D50-15FX	D80-15FX	D100-15FX
Capacitate (litri)	50	80	100
Putere nominala (W)	1500	1500	1500
Dimensiuni exterioare H x D (mm)	Ø385x757	Ø450x818	Ø450x976
Panou Control	ELECTRONIC	ELECTRONIC	ELECTRONIC
Tip Termostat	Termostat Capilar	Termostat Capilar	Termostat Capilar
Interval Temperatura (°C)	30- 75	30- 75	30- 75
Presiune Lucru Maxima (Mpa)	0.75	0.75	0.75
Indicator Temperatura	Da	Da	Da
Indicator Incalzire	Da	Da	Da
Indicator Alimentare	Da	Da	Da
Protectie Supraincalzire	Da	Da	Da
Temperatura Maxima	101	101	101
Rezervor Interior	Rezervor emailat	Rezervor emailat	Rezervor emailat
Tip de Acoperire	Email	Email	Email
Grosimea Medie a Izolatiei (mm)	18	18	18
Densitatea Izolatiei (Kg/m ³)	33-35	33-35	33-35
Dimensiuni Anod de Magneziu (mm)	φ18*110	φ18*110	φ18*110
Tip element incalzire	Otel inox SUS 316L emailat	Otel inox SUS 316L emailat	Otel inox SUS 316L emailat
Lungime cablu alim. (m)	1.5	1.5	1.5
Montaj standard	Vertical	Vertical	Vertical

- ☞ **5 ani garantie rezervor apa**
- ☞ **rezervor emailat prin sinterizare la 850°C pe substrat de titan**
- ☞ **conducta de intrare antibacteriana cu ioni de Ag+**
- ☞ **99% rata de succes impotriva bacteriilor**

